

### INTENDED USES

For use in dry and wet work areas. Its modular style with hidden interlocks is very versatile and can even cover an entire floor. And the light-weight design facilitates maintenance, but doesn't scrimp on comfort.

### DETAILS AND COMPOSITION

<b>Compound</b>	50% Nitrile Rubber r
<b>Edges</b>	Safety rounded
<b>Thickness</b>	1/2"
<b>Overall Weight</b>	1.6 lbs. sq. ft or 14.6 lbs. per mat
<b>Size</b>	3' x 3'
<b>Custom Sizes</b>	Up to 12' wide x up to 60' long in one piece, other sizes available
<b>Color</b>	Black

### TEST SPECIFICATIONS AND RESULTS

Property	Test	Results
<b>Flammability (surface)</b>	MVSS 302	"A" Rating. It has a flame spread of < 1.6 and is labeled self-extinguishing.
<b>Coefficient of Friction</b>	ASTM F1677	Dry: COF = >.84 Wet: COF = .78 Oily: COF = .34
<b>Impact Absorption</b>	ASTM F355	Peak Deceleration 11.9g Duration, Msec 185.0
<b>Compression Deflection</b>	ASTM D575	Deflection @35 psi, mm = 4.10
<b>Abrasion Resistance</b>	ASTM C501	Wear Index, 1/g = 59
<b>Ozone Resistance</b>	ASTM D 1171	Excellent
<b>Temperature Range</b>	ASTM D 1056	-50 to 250 degrees Fahrenheit
<b>Durometer</b>	ASTM D2240	55

### CHEMICAL RESISTANCE (SURFACE)

Chemical	Ranking	Chemical	Ranking
Acetic Acid 30%	Fair	Hydrogen Peroxide (dilute)	Good
Acetone	Fair	Nitric Acid 30%	NR
Butyl Alcohol	Great	Sodium Hydroxide	Good
Carbon Tetrachloride	NR	Sulfuric Acid (dilute)	Poor
Detergent Solution	Good	Water	Great

**Note:** Please call for additional results, technical assistance or to request a small sample for testing.

## CLEANING RECOMMENDATIONS

Use a high-pressure hose (not to exceed 500 psi) and hot water (max 160 degrees F) to rid the mats of oils. For best results use a mild soap or detergent like Ivory Liquid with a ph between 4.0 – 9.0, to clean the mats. Do not use steam, degreasers or caustic chemicals. Do not machine wash or mechanically scrub the mats.

## HOW TO REACH US

For more information or to place an order, call 1-800-264-3030. To view this product in color, please visit our website, [www.wearwell.com](http://www.wearwell.com).

## LIMITED WARRANTY

### Limited Warranty

The materials and workmanship used in the construction of all Wearwell® Mats are guaranteed under normal conditions of usage for **one year** after the date of shipment. If the purchaser discovers a defect in the materials or workmanship of a Wearwell® mat within the warranted time after the date of shipment, Tennessee Mat Company, Inc. will, at its own discretion, either i.) repair the nonconforming product, ii.) replace the product with the same or substantially similar product, or iii.) reimburse the buyer for the pro-rated purchase price of the nonconforming product.

Tennessee Mat Company reserves the right to inspect the non-conforming mat(s) before repairing, replacing or reimbursing the buyer. Therefore, at the preference of Tennessee Mat Company, Inc., the mats must be returned or available for on-site inspection. Modifying or installing the mat may void the warranty. The decision to void this warranty will be made at the sole discretion of Tennessee Mat Company.

To the maximum extent permitted by law, Tennessee Mat Company's liability shall not exceed the purchase price of the product; Tennessee Mat Company shall not be liable for any incidental, consequential, special, and indirect or punitive damages (including without limitation, damages from lost business, profits or goodwill).