



www.wearwell.com

24/Seven GR (Grease Resistant) Male Edging - Yellow

Group 572-MGRYL

24/Seven GR (Grease Resistant) male edging securely interlocks with 24/Seven GR rubber floor tiles. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

la Catégorie Anti-Fatigue Flooring

Environnement Convient Sec, Humide, Glissant

Personnalisation Niveau C3 - Full Custom (Length, Width, Shape)

Drainage ou solide Solid

Composé Grease Resistant Natural Rubber (GR)

Recyclé >50%

Garantie 1 Year

Property	Test / Result
Inflammabilité	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Température ambiante	10 to 140 F
Coefficient de frottement	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
Débattement de compression	Not Available
La force des larmes	Not Available
Estimation d'ESD	Not Available
Rigidité diélectrique	Not Available

Numéro de la pièce	UPC	Couleur	Épaisseur	Dimensions	Partie courante	UOM
--------------------	-----	---------	-----------	------------	-----------------	-----