



www.wearwell.com

24/Seven CFR Bordure mâle, noir

Group 572-MCFRBK

24/Seven CFR (Cutting Fluid Resistant) male edging securely interlocks with 24/Seven CFR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

la Catégorie Anti-Fatigue Flooring

Environnement Convient Sec, Humide, Huileux, Glissant

Personnalisation Niveau C3 - Full Custom (Length, Width, Shape)

Drainage ou solide Solid

Composé Cutting Fluid Resistant Rubber (CFR)

Recyclé >50%

Garantie 1 Year

Property	Test / Result
Inflammabilité	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss Temperature Range
Température ambiante	10 to 140 F
Coefficient de frottement	ASTM F1677 / Dry: COF = .90 / Wet COF = 0.20
Débattement de compression	Not Available
La force des larmes	Not Available
Estimation d'ESD	Not Available
Rigidité diélectrique	Not Available

Numéro de la pièce	UPC	Couleur	Épaisseur	Dimensions	Partie courante	UOM
--------------------	-----	---------	-----------	------------	-----------------	-----