



www.wearwell.com

24/Seven CFR Bordure femelle, noir

Group 572-FCFRBK

24/Seven CFR (Cutting Fluid Resistant) female edging securely interlocks with 24/Seven CFR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

la Catégorie Anti-Fatigue Flooring

Environnement Convient Sec, Humide, Huileux, Glissant

Personnalisation Niveau C3 - Full Custom (Length, Width, Shape)

Drainage ou solide Solid

Composé Cutting Fluid Resistant Rubber (CFR)

Recyclé >50%

Garantie 1 Year

Property	Test / Result
Inflammabilité	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Température ambiante	10 to 140 F
Coefficient de frottement	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
Débattement de compression	Not Available
La force des larmes	Not Available
Estimation d'ESD	Not Available
Rigidité diélectrique	Not Available

Numéro de la pièce	UPC	Couleur	Épaisseur	Dimensions	Partie courante	UOM
--------------------	-----	---------	-----------	------------	-----------------	-----