



www.wearwell.com

FOUNDATION™ Modular Aluminum Work Platforms for Injection Molding

Group FPIM

In many injection molding environments, reach isn't the only concern. The presence of grease and hydraulic fluids introduces slip and fall hazards. Injection molding operators need both the proper work height and the proper work surface. Wearwell engineered modular [work platforms](#) to do both. Get the [FOUNDATION™](#) platform that meets your environment.

As a fully modular system, FOUNDATION cuts down on the time, labor, customization, and costly manpower of traditional work platforms. **Assembly and installation have never been easier!** Choose from a range of heights, lengths, and widths to form any shape and size down to 18" (.45m) sections.

All components of FOUNDATION, including the stout aluminum frame, are corrosion-resistant. The 100% recycled polypropylene tiles stand up to grease, oils, and hydraulic fluids. Each 18" x 18" tile boasts a load rating of 400 pounds, providing all the support your operators need and more.

- Better ergonomics for workers
- Superior traction
- Abrasion resistant
- Broad spectrum of chemical resistance
- 400 lb. (181.5kg) load capacity per tile

la Catégorie	Platform
Environnement Convient	Sec
Personnalisation Niveau	C3
Drainage ou solide	Drainage
Composé	Polypropylene/Aluminum
Recyclé	54%
Garantie	1 year

Property	Test / Result
Inflammabilité	FMVSS 302: Pass SE/(B)
Taber Abrasion	ASTM D3884: 0% @1000 cycles
Température ambiante	32-160F
Coefficient de frottement	ASTM F2913-19: 0.79 dry, 0.62 wet
Débattement de compression	Not Applicable
La force des larmes	Not Applicable
Estimation d'ESD	Not Applicable
Rigidité diélectrique	Not Applicable

Numéro de la pièce	UPC	Couleur	Épaisseur	Dimensions	Partie courante	UOM
--------------------	-----	---------	-----------	------------	-----------------	-----