



<https://wearwell.com/>

24/Seven® Solid w/ Gritshield® CFR - Interlocking Rubber Floor Tiles 3' x 3'

Group 574-CFR

WHILE SUPPLIES LAST!

[Contact us for pricing](#)

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges.

◦ Available in 3 different rubber compounds based on environmental exposures:

- GR - for water or dry debris
- CFR - for mineral oil-based fluids
- NBR - for petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors, Wet Area, Oily, Slippery

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material Cutting Fluid Resistant Rubber (CFR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet: COF = .68
Compression Deflection	ASTM D 575 / Deflection @35 psi, mm= 8.02, inches = .315
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
574.58x3x3CFRBK	715411893317	Black	5/8 In. (16 mm)	3' x 3'	Y	EA

