



<https://wearwell.com/>

24/Seven Open CFR - Interlocking Rubber Floor Tiles 3' x 3'

Group 572-CFR

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges.

- Available in 3 different rubber compounds based on environmental exposures:
 - GR - for water or dry debris
 - CFR - for mineral oil-based fluids
 - NBR - for petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12" (30 cm) increments
 - Holes are 11/16" wide
 - Overall thickness 5/8" (16 mm)

Wearwell Categories	Anti-Fatigue Flooring
Suitable Environment	Dry Floors, Wet Area, Oily, Slippery
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Cutting Fluid Resistant Rubber (CFR)
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
572.58x3x3CFRFBK	715411572342	Black	5/8 In. (16 mm)	3' x 3'	Y	EA

