WEARWELL



https://wearwell.com/

ErgoDeck Smooth Heavy Duty

Group 569

Ideal for <u>cart traffic</u> and pivoting, ErgoDeck Smooth[™] Heavy Duty is a robust, high performance solution for wheeled traffic that makes moving heavy loads easier than ever! Unlike soft mats that deform under load, ErgoDeck Smooth features a lightly textured surface that is easy to clean but without compromising traction. Optional 6" (22 cm) wide ramps are cart friendly, allowing easy on-off access.

- U.S. PATENT NO. D502,557; D520,650
- Slight textured surface is ideal for push carts and pivoting
- Customize in 3" (8 cm) increments to fit any area or configuration
- LockSafe Positive Interlocking System[™] prevents separation
 Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)
- Available in Black or Charcoal

Learn more about ErgoDeck ergonomic flooring here.

Wearwell Categories	Anti-Fatigue Flooring
Suitable Environment	Dry Floors, Wet Area, Oily
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC
Recycled	>80%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF =.65 / Wet: COF = .42
Compression Deflection	ASTM D575 - 82.2 psi @ 15% =.20" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
569.78x18x18BK-CS10	715411169834	Black	7/8 In. (22 mm)	18" x 18"	Y	CS-10
569.78x18x18CH-CS10	715411169834	Charcoal	7/8 In. (22 mm)	18" x 18"	Y	CS-10