



<https://wearwell.com/>

## ErgoDeck General Purpose - Smooth Anti-Fatigue Flooring

### Group 568

Smooth, General Purpose ErgoDeck is **a comfortable, ergonomic floor with long-lasting performance.** The 18" x 18" modular tiles feature patented LockSafe interlocks that deliver secure connections but can be taken apart and repositioned as workflow and operations change.

Unlike soft mats that deform under load, Smooth ErgoDeck General Purpose features a firm, lightly textured surface that's ideal for [light cart and wheeled traffic](#) but without compromising traction.

The softer, General Purpose compound and box spring structure are engineered to provide greater impact absorption and ergonomic support. Optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation.

- U.S. PATENT NO. D502,557; D520,650
- Lightly textured surface is ideal for push carts and pivoting
- Customize in 3" (8 cm) increments to fit any area or configuration
- [LockSafe Positive Interlocking System™](#) prevents separation
- Fast installation saves downtime
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)
- Available in Black or Charcoal

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry Floors, Wet Area, Oily

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Material** PVC

**Recycled** >80%

**Warranty** Lifetime

| Property                | Test / Result                                       |
|-------------------------|-----------------------------------------------------|
| Flammability            | MVSS 302 / 'A'; Rating                              |
| Taber Abrasion          | ASTM D 3884 / 1% loss                               |
| Temperature Range       | 0 to 140 F                                          |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .65 / Wet: COF = .42        |
| Compression Deflection  | ASTM D575 - 70 psi @ 15% = .20" distance compressed |
| Tear Strength           | Not Available                                       |
| ESD Rating              | Not Available                                       |
| Dielectric Strength     | Not Available                                       |

| SKU                 | UPC          | Color | Thickness       | Dimensions | Stock Part | UOM   |
|---------------------|--------------|-------|-----------------|------------|------------|-------|
| 568.78x18x18BK-CS10 | 715411698325 | Black | 7/8 In. (22 mm) | 18" x 18"  | Y          | CS-10 |