



<https://wearwell.com/>

ErgoDeck® General Purpose Solid with Gritshield®

Group 567

A high traction, ergonomic floor that will withstand heavy use. The [LockSafe Positive Interlocking System](#) delivers secure connections. Perfect for [lean manufacturing](#), tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose with GRITSHIELD increases traction by 40% and addresses worker health and comfort in areas with primarily foot traffic and light cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Softer compound for greater standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and [Drainage](#) version and with GRITSHIELD for extra traction
- Overall thickness 7/8"

Learn more about the benefits of ErgoDeck in our blog - [Top 6 Benefits of ErgoDeck Anti-Fatigue Floors](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Wet Area, Oily, Slippery

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material PVC

Recycled >80%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	0 to 140 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	ASTM D575 - 62.2 psi @ 15% = .22" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
567.78x18x18CH-CS10	715411060023	Charcoal	7/8 In. (22 mm)	18" x 18"	Y	CS-10