



<https://wearwell.com/>

## ErgoDeck® Heavy Duty Solid with Gritshield®

### Group 563

A slip-resistant ergonomic floor that will withstand heavy use. The [LockSafe Positive Interlocking System](#) delivers secure connections. Perfect for [lean manufacturing](#), tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. Available in a solid and drainage version, ErgoDeck Heavy-Duty with GRITSHIELD delivers 40% more traction and withstands heavy use and [cart traffic](#).

- U.S. PATENT NO. D502,557; D520,650
- Secure footing in slippery applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Learn more about the different versions of ErgoDeck in our blog - [ErgoDeck Ergonomic Interlocking Floor Tiles - Which Version Should I Choose?](#)

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Wet Area, Oily, Slippery

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Material** PVC

**Recycled** >80%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	ASTM D575 - 82.2 psi @ 15% = .13" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
563.78x18x18BK-CS10	715411570904	Black	7/8 In. (22 mm)	18" x 18"	Y	CS-10