



<https://wearwell.com/>

## ErgoDeck® Heavy Duty Open with Gritshield®

### Group 561

ErgoDeck® Heavy Duty Open with GRITSHIELD® is a dependable, slip resistant floor that facilitates drainage and will withstand heavy use. The [LockSafe Positive Interlocking System](#) delivers secure connections. Perfect for [lean manufacturing](#), tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck Heavy Duty is the best choice in areas with heavy cart and foot traffic. Why? The firmer compound lets carts roll over the tiles with ease. Meanwhile, the underside box-spring design provides structural support and impact absorption for health and comfort, even in multi-shift operations.

- U.S. PATENT NO. D502,557; D520,650
- Secure footing in slippery applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version
- Overall thickness 7/8"
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Learn more about the different versions of ErgoDeck in our blog [ErgoDeck Ergonomic Interlocking Floor Tiles – Which Version Should I Choose?](#)

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Wet Area, Oily, Slippery

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Drainage

**Material** PVC

**Recycled** >80%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	ASTM D575 - 85 psi @ 15% = .13" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
561.78x18x18BK-CS10	715411568413	Black	7/8 In. (22 mm)	18" x 18"	Y	CS-10

