



<https://wearwell.com/>

Rejuvenator Interlocking Tile

Group 502-F

Rejuvenator Flooring features large 3'x3' modules--and now new 1'x3' modules as well-- that interlock on all 4 sides to customize on-site virtually any flooring configuration. The interlock is incredibly effective--and also hidden--so the ergonomic floor you've created is seamless and stable underfoot. Having the ability to customize in 1 foot increments and finish off with beveled ramps [yellow or black] sets Rejuvenator Flooring apart from all other urethane "wannabees".

- U.S. PATENT NO. D653,893
- Meets the ASTM G21 standard for anti-microbial properties
- Configure large areas quickly
- Deep Positive Lock keeps seams secure
- Tiles are 100% Urethane with thick outer wear layer
- Ramps are 100% SBR Rubber
- Customizable in 1' increments
- Overall thickness 5/8"

Learn more about Rejuvenator flooring and matting [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material Polyurethane

Recycled <10%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	-50 to 250 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .75 / Wet: COF = .28
Compression Deflection	ASTM D575 - 5.9psi @ 25% =.17" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
502.58x1x3BK	715411004584	Black	5/8 In. (16 mm)	1' x 3'	Y	EA
502.58X3X3BK	715411284306	Black	5/8 In. (16 mm)	3' x 3'	Y	EA