



<https://wearwell.com/>

24/Seven® LockSafe® Interlocking Rubber Floor Tiles - Drainage NBR w/ Gritshield®

Group 586-NBR

[Slip prevention](#) and anti-fatigue in one. 24/SEVEN® LockSafe® NBR with GRITSHIELD® is ideal for high chemical resistance in high-demand areas. The open-style surface is ideal for slippery areas that require [drainage](#). These large 3'x3' rubber tiles interlock and require no tools making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them. The Positive Interlock System provides a secure connection in all directions, so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

- U.S. PATENT NO. D882,293 S
- Ideal for oily, greasy, high-demand areas
- Hidden positive interlocking system
- Choose GRITSHIELD for increased traction
- Choice of [solid](#) or drainage style
- Create your own custom widths or lengths in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Learn more about 24/SEVEN LockSafe [here](#).

Wearwell Categories	Anti-Fatigue Flooring
Suitable Environment	Dry Floors, Wet Area, Oily, Slippery
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Nitrile Rubber (NBR)
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.1 / Wet COF = .96
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
586.58x3x3NBRBK	715411702930	Black	5/8 In. (16 mm)	3' x 3'	Y	EA

