



<https://wearwell.com/>

24/Seven® LockSafe® Interlocking Rubber Floor Tiles - Solid NBR w/ Gritshield®

Group 584-NBR

[Slip prevention](#) and anti-fatigue in one. 24/SEVEN® LockSafe® NBR with GRITSHIELD® is ideal for high chemical resistance in high-demand areas. The solid surface is ideal for foot or [cart traffic](#) in slippery environments. These large 3'x3' rubber tiles interlock and require no tools making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them.

The Positive Interlock System provides a secure connection in all directions, so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

- U.S. PATENT NO. D882,293 S
- Ideal for oily, greasy, high-demand areas
- Hidden positive interlocking system
- Choose GRITSHIELD for increased traction
- Choice of solid or [drainage](#) style
- Create your own custom widths or lengths in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Learn more about 24/SEVEN LockSafe [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors, Wet Area, Oily, Slippery

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.1 / Wet COF = .91
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
584.58x3x3NBRBK	715411702916	Black	5/8 In. (16 mm)	3' x 3'	Y	EA

