WEARWELL



https://wearwell.com/

24/Seven® LockSafe® Drainage NBR -Interlocking Rubber Floor Tiles 3' x 3'

Group 578-NBR

Performance meets comfort for wet, oily environments. 24/SEVEN LockSafe NBR is ideal for high chemical resistance in high-demand areas. The Nitrile rubber compound is ideal for harsh environments and the open design allows for optimum drainage.

These large 3'x3' rubber tiles require no tools for assembly making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them.

The Positive Interlock System provides a secure connection in all directions so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

- U.S. PATENT NO. D882,293 S
- Made for oily, greasy, high-demand areas
- Large 3 ft x 3 ft tiles
- Hidden positive interlocking system
- Choice of solid or drainage style
- Choose GRITSHIELD for increased traction
- Create your own custom widths or lengths in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Wearwell Categories	Anti-Fatigue Flooring
Suitable Environment	Dry Floors, Wet Area, Oily, Slippery
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Nitrile Rubber (NBR)
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .84 / Wet: COF = .45
Compression Deflection	ASTM D575 - 16.5 psi @ 25% =.13" distance compressed
Tear Strength	Not Available
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM

578.58x3x3NBRBK 7154117	703081 Black	5/8 In. (16 mm)	3' x 3'	Y	EA
-------------------------	--------------	-----------------	---------	---	----