



<https://wearwell.com/>

ErgoDeck MAX Smooth Design

Group 600

Gone are the days of having to choose between comfort and customization. Introducing a modular tile that takes flexibility, performance and safety to the max - ErgoDeck MAX. ErgoDeck Max with [LockSafe](#) technology holds secure but can be taken apart and reconnected on demand. This revolutionary product utilizes a universal edging system for simple configuration and installation. Each section features counter sunk holes for semi-permanent installations and traction bars for added [slip prevention](#). ErgoDeck Max carries a Limited-Lifetime Warranty.

- Durable ErgoDeck surfaces
- NFSI Certified
- Nitricell premium sponge core
- Easy to install, universal ramps
- 100% Silicone Free
- Overall thickness 7/8" (22 mm)
- U.S. PATENT NO. 10,914,081; 11,174,648; D502,557; D520,650; 11,454,037

Learn more about ErgoDeck MAX [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage

Material PVC/Nitrile Sponge

Recycled <30%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Applicable
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .95 / Wet: COF = .65
Compression Deflection	ASTM D575 - 8.3psi @ 25% = .23" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
600.78x18x18BK-CS10	715411698424	Black	7/8 In. (22 mm)	18" x 18"	Y	CS-10
600.78x18x18CH-CS10	715411698431	Charcoal	7/8 In. (22 mm)	18" x 18"	Y	CS-10