



<https://wearwell.com/>

24/Seven® LockSafe® Open ESD - Interlocking GR Rubber Floor Tiles

Group 772-GR

Static Electricity can produce damaging sparks that can ruin and destroy expensive equipment. 24/SEVEN LockSafe Open [ESD](#) eliminates static while providing a drainage ergonomic work surface for your team to perform. Made to cover large areas quickly, the 772 ESD can be placed directly atop a conductive coating or floor, eliminating the need for messy grounding cords. For more conventional installations, each tile comes with the grounding snap already installed for use with a grounding cord. The 'positive interlock' technology allows the rubber tiles to lock in while remaining easy enough to 'unzip' for reconfiguration. Around electronics keeping a work area clean is very important. The [LockSafe](#) connection system allows the mat to be rolled up to make keeping a cleaning easier.

NOTE: Unless used over a conductive floor, mats must be grounded with a ground cord ([793-Cord](#)) and users must wear a heel grounder ([793-Heel](#))

- EOS/ESD S7.1: $1 \times 10^6 - 1 \times 10^9$
- Meets ANSI/ESD 20.20 requirements
- 5/8" thick, 3' wide
- Made in USA

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors, Wet Area, Slippery

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Drainage

Material Grease Resistant Natural Rubber (GR)

Recycled <50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'B'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = .94
Compression Deflection	ASTM D575 - 21.9psi @ 25% = .16" distance compressed
Tear Strength	Not Applicable
ESD Rating	EOS/ESD S7.1: $1 \times 10^6 - 1 \times 10^9$ (meets ANSI/ESD 20.20 requirements)
Dielectric Strength	Not Applicable

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
772.58x3x3GRBK	715411012022	Black	5/8 In. (16 mm)	3' x 3'	Y	EA