



<https://wearwell.com/>

24/Seven® LockSafe® DP - Grease Resistant Anti-Fatigue Flooring - For Welding

Group 579W

Performance meets comfort in gas arc welding. 24/Seven LockSafe is a modular ergonomic floor system made up of large 3' x 3' rubber tiles that install fast and stay secure. The iconic diamond-plate surface provides additional traction for stability and the pliable rubber compound provides the comfort MIG and TIG welders need to maintain focus.

24/Seven's LockSafe connections hold secure in all directions with no fear of separation even with heavy foot traffic or light cart traffic. The dependable interlocks, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. These tiles stay together but can be "unzipped" when needed.

Use optional 24/Seven GR edging and corners for a safe transition in and out of welding workstations and booths.

- U.S. PATENT NO. D882,293 S
- Fast installation; no tools required
- Reliable connections
- Can be cut and reconnected every 12" (30 cm)
- Overall thickness 5/8" (16 mm)

Learn more about welding matting and flooring solutions [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors, Wet Area, Slippery

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material Grease Resistant Natural Rubber (GR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.0 / Wet COF = .79
Compression Deflection	ASTM D575 - 21.9 psi @ 25% = .16" distance compressed
Tear Strength	NA
ESD Rating	NA
Dielectric Strength	NA