



<https://wearwell.com/>

Standard Corrugated Vinyl

Group 381

Our most popular runner, Standard Corrugated Vinyl protects floors, reduces cleaning costs and adds traction wherever needed. Sleek corrugated pattern adds a professional finish.

- Sleek corrugated surface protects floors
- 1/8" (3 mm) thick
- Easy to clean, chemically resistant surface
- Vinyl compound won't curl

Wearwell Categories Runner

Suitable Environment Dry Floors

Customization Options Standard Sizes Only

Solid or Drainage Solid

Material PVC

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	-10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .91 / Wet: COF = .65
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
381.18x2x105BK	715411502929	Black	1/8 In. (3 mm)	2' x 105'	Y	RL
381.18x2x150BK	715411502806	Black	1/8 In. (3 mm)	2' x 150'	Y	RL
381.18x2x75BK	715411429219	Black	1/8 In. (3 mm)	2' x 75'	Y	RL
381.18x3x105BK	715411503223	Black	1/8 In. (3 mm)	3' x 105'	Y	RL
381.18x3x150BK	715411503100	Black	1/8 In. (3 mm)	3' x 150'	Y	RL
381.18x3x75BK	715411429226	Black	1/8 In. (3 mm)	3' x 75'	Y	RL
381.18x4x105BK	715411503520	Black	1/8 In. (3 mm)	4' x 105'	Y	RL
381.18x4x150BK	715411503407	Black	1/8 In. (3 mm)	4' x 150'	Y	RL
381.18x4x75BK	715411429233	Black	1/8 In. (3 mm)	4' x 75'	Y	RL