



<https://wearwell.com/>

WeldSafe®

Group 447

Specially compounded SBR rubber surface outperforms all other anti-fatigue matting in spot-welding applications and repels sparks and hot metal shards. The Nitricell sponge base offers unparalleled resilience and comfort.

- Fully Customizable - any shape, size, or configuration
- High heat, spark resistant rubber surface
- Nitrile blend anti-fatigue sponge for ergonomic support
- Ideal for welding areas, booths, and workstations
- Ignition point of over 500 degrees Fahrenheit
- National Floor Safety Institute Certified
- Flammability: MVSS 302: "A" Rating
- Made in the USA
- Available in 1" (2.54 cm) and 11/16" (1.75 cm) thick
- #1 Wearwell Brand since 1950

◦ **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Welding Mats in our blog - [Best Welding Mats - 6 Things to Consider](#).

Wearwell Categories Mat

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material Natural Rubber Surface

Recycled >20%

Warranty 4 Years

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	500 F Melt Point
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.1+ / Wet COF = .89
Compression Deflection	ASTM D575 - Ultra 7psi @ 25% =.21" distance compressed, Standard 9.4psi @ 25% =.14" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
447.78x2x3BK	715411046416	Black	1 In. (25 mm)	2' x 3'	Y	EA
447.78x2x75BK	715411046423	Black	1 In. (25 mm)	2' x 75'	N	RL
447.78x3x5BK	715411046447	Black	1 In. (25 mm)	3' x 5'	Y	EA
447.78x3x75BK	715411046454	Black	1 In. (25 mm)	3' x 75'	Y	RL

447.78x4x75BK	715411046478	Black	1 In. (25 mm)	4' x 75'	N	RL
447.916x2x3BK	715411447220	Black	11/16 In. (17 mm)	2' x 3'	Y	EA
447.916x2x75BK	715411447213	Black	11/16 In. (17 mm)	2' x 75'	N	RL
447.916x3x5BK	715411447350	Black	11/16 In. (17 mm)	3' x 5'	Y	EA
447.916x3x75BK	715411447756	Black	11/16 In. (17 mm)	3' x 75'	Y	RL
447.916x4x75BK	715411447152	Black	11/16 In. (17 mm)	4' x 75'	N	RL