



Ortho Stand™

Group 454

Ideal for commercial and light industrial applications, the hollow-domed surface slightly compresses underfoot to fight fatigue.

- Economical
- Enhanced anti-fatigue properties
- Available with black or yellow borders
- Overall thickness 1/2"

<https://wearwell.com/>

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors, Wet Area
Customization Options	Standard Sizes Only
Solid or Drainage	Solid
Material	Grease Resistant Natural Rubber
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Available
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90 / Wet: COF = .36
Compression Deflection	ASTM D575 - 7.3psi @ 25% = .13" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
454.12x2x3BK	715411304752	Black	1/2 In. (13 mm)	2' x 3'	Y	EA
454.12x2x3BYL	715411304783	Black/Yellow	1/2 In. (13 mm)	2' x 3'	Y	EA
454.12x3x4BK	715411304813	Black	1/2 In. (13 mm)	3' x 4'	Y	EA
454.12x3x4BYL	715411304844	Black/Yellow	1/2 In. (13 mm)	3' x 4'	Y	EA