



WorkSafe® Grease Resistant

Group 477

Available as single workstation mats or can be attached together with connector strips to form virtually any size or configuration.

- Versatile configuration
- Wide array of connectable sizes
- Natural rubber
- Overall thickness 7/8"

<https://wearwell.com/>

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors, Wet Area
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Grease Resistant Natural Rubber
Recycled	>33%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90
Compression Deflection	ASTM D575 - 15.9psi @ 25% = .21" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
477.78x18x24GRBK	715411585816	Black	7/8 In. (22 mm)	18" x 24"	Y	EA
477.78x18x48GRBK	715411587322	Black	7/8 In. (22 mm)	18" x 48"	Y	EA
477.78x2x3GRBK	715411585854	Black	7/8 In. (22 mm)	2' x 3'	Y	EA
477.78x3x30GRSBK	715411305629	Black	7/8 In. (22 mm)	3' x 30"	Y	EA
477.78x3x4GRBK	715411586301	Black	7/8 In. (22 mm)	3' x 4'	Y	EA
477.78x3x5GRSBK	715411305681	Black	7/8 In. (22 mm)	3' x 5'	Y	EA
477.78x3x5SFGRBK			7/8 In. (22 mm)	91 cm x 152 cm	Y	EA