



## WorkSafe® Light CFR

### Group 478

An ideal anti-fatigue mat for wet industrial areas, WorkSafe Light has a well-engineered drainage system and molded-in edges provide safe access.

- Lightweight
- High Performance
- Cutting Fluid Resistant
- Overall thickness 1/2"

<https://wearwell.com/>

<b>Wearwell Categories</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Wet Area, Oily
<b>Customization Options</b>	Standard Sizes Only
<b>Solid or Drainage</b>	Drainage
<b>Material</b>	Cutting Fluid Resistant Rubber
<b>Recycled</b>	<10%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Available
Temperature Range	10 to 250 F
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90 / Wet: COF = .34
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=4.10
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
478.12x3x10GY	715411536603	Gray	1/2 In. (13 mm)	3' x 10'	Y	EA
478.12x3x20GY	715411536030	Gray	1/2 In. (13 mm)	3' x 20'	Y	EA
478.12x3x5GY	715411538010	Gray	1/2 In. (13 mm)	3' x 5'	Y	EA