



Abrasive Coated Kushion Walk Unslotted

Group 480-UNS

KushionWalk's high quality PVC formulation and tough construction are ideal for heavy use areas.

- Industrial tough and abrasion resistant
- Durable textured surface guards against slipping
- Highly cut resistant. Excellent choice for covering grated walkways
- Also available in drainage version
- Overall thickness 3/8"

<https://wearwell.com/>

Wearwell Categories Industrial Runner

Suitable Environment Wet Area, Oily, Slippery

Customization Options C1 - Custom Length

Solid or Drainage Solid

Material PVC

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.03 / Wet: COF = .81
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
480.38x2x60UNSBK	715411404155	Black	3/8 In. (10 mm)	2' x 60'	N	RL
480.38x3x60UNSBK	715411404391	Black	3/8 In. (10 mm)	3' x 60'	Y	RL