

## 24/Seven LockSafe Grease Resistant Female Edging



### Group 578-RFGR

24/Seven LockSafe female edging is Grease Resistant and securely interlocks with 24/Seven LockSafe modular tiles. Black edging creates a seamless and smooth transition for foot traffic.

Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

<https://wearwell.com/>

- Grease Resistant Natural Rubber (GR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and Male Edging available
- Available in black and yellow

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry Floors, Wet Area, Slippery

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Material** Grease Resistant Natural Rubber (GR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable