



<https://wearwell.com/>

24/Seven LockSafe Nitrile Rubber (NBR) Corner - Case of 4

Group ML578-RMNBR

Performance meets comfort for wet, oily environments. **24/SEVEN LockSafe Interlocking Rubber Mats are Grease Proof (NBR) for high chemical resistance in high-demand areas.** The Nitrile rubber compound is ideal for harsh environments and the open design allows for optimum drainage. These large 3'x3' rubber tiles require no tools for assembly making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them.

- Nitrile Rubber (NBR)
- Ideal for oily

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors, Wet Area, Oily, Slippery

Customization Options C3 - Full Custom (Length

Solid or Drainage Solid

Material Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable