



<https://wearwell.com/>

## Tile-Top Select - Gray Anti Fatigue Mats

### Group 494GY

**Provide fatigue relief for your workers** that are on their feet all day. Tile-Top Select [anti-fatigue](#) floor mats make an economical and comfortable anti-fatigue flooring solution. The chemical resistant PVC surface and FlexLink sponge base delivers **outstanding ergonomic support**.

Tile-Top Select is a perfect choice for medical, pharmacy, and lab applications because the composition of this mat results in anti-microbial characteristics with **NO SPECIAL ADDITIVES** required. This inhibits the growth of organic compounds and bacteria, keeping your standing area more hygienic. Comes in classic marbled style and colors to complement any office, commercial or industrial environment.

- Durable, easy to clean marbled style surface
- Flex-Link sponge base is economical and comfortable
- Floor mat provides anti-fatigue and ergonomic support for standing workers
- Ideal for light industrial or commercial applications
- Convenient sizes for workstations, standing height desks
- Meets the ASTM G21 standard for anti-microbial properties
- Available in multiple marble top colors & sizes
- Available in 1/2" and 7/8" thick

Learn more about Tile-Top ergonomic matting [here](#).

|                              |                             |
|------------------------------|-----------------------------|
| <b>Wearwell Categories</b>   | Anti-Fatigue Matting        |
| <b>Suitable Environment</b>  | Dry Floors                  |
| <b>Customization Options</b> | C1 - Custom Length          |
| <b>Solid or Drainage</b>     | Solid                       |
| <b>Material</b>              | PVC Surface With PVC Sponge |
| <b>Recycled</b>              | <10%                        |
| <b>Warranty</b>              | 3 Years                     |

| Property                | Test / Result                               |
|-------------------------|---|
| Flammability            | MVSS 302 / 'A'; Rating                      |
| Taber Abrasion          | ASTM D 3884 / 1% loss                       |
| Temperature Range       | 0 to 110 F                                  |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .78 / Wet COF = .17 |
| Compression Deflection  | ASTM D395-98 / 30%                          |
| Tear Strength           | Not Available                               |
| ESD Rating              | Not Available                               |
| Dielectric Strength     | Not Available                               |

| SKU           | UPC          | Color | Thickness       | Dimensions | Stock Part | UOM |
|---------------|--------------|-------|-----------------|------------|------------|-----|
| 494.12x2x3GY  | 715411256105 | Gray  | 1/2 In. (13 mm) | 2' x 3'    | Y          | EA  |
| 494.12x2x60GY | 715411334117 | Gray  | 1/2 In. (13 mm) | 2' x 60'   | Y          | RL  |

|               |              |      |                 |          |   |    |
|---------------|--------------|------|-----------------|----------|---|----|
| 494.12x3x5GY  | 715411256525 | Gray | 1/2 In. (13 mm) | 3' x 5'  | Y | EA |
| 494.12x3x60GY |              | Gray | 1/2 In. (13 mm) | 3' x 60' | Y | RL |
| 494.12x4x60GY | 715411332342 | Gray | 1/2 In. (13 mm) | 4' x 60' | Y | RL |
| 494.78x2x3GY  | 715411117536 | Gray | 7/8 In. (22 mm) | 2' x 3'  | Y | EA |
| 494.78x2x60GY |              | Gray | 7/8 In. (22 mm) | 2' x 60' | Y | RL |
| 494.78x3x5GY  | 715411118335 | Gray | 7/8 In. (22 mm) | 3' x 5'  | Y | EA |
| 494.78x3x60GY |              | Gray | 7/8 In. (22 mm) | 3' x 60' | Y | RL |
| 494.78x4x60GY |              | Gray | 7/8 In. (22 mm) | 4' x 60' | Y | RL |