



<https://wearwell.com/>

UltraSoft Diamond-Plate SpongeCote - Black with Chevron Borders

Group 414CHV

Designed for comfort and optimized worker productivity, these mats are exceedingly popular among standing workers and have industrial strength for multiple shift operations. The double-thick Nitricell sponge base is a Nitrile composite for exceptional comfort, rebound and long life.

- NFSI Certified
- Nitricell sponge base
- 15/16" overall thickness
- Maximized standing area
- Also available in gray, black and black with yellow borders
- **Need a different size?** 1' incremental lengths are available! [Simply give us a call, and we can help!](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material PVC Surface With Nitrile Infused Sponge

Recycled >50%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 - 6.2psi @ 25% = .24" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
414.1516x2x3CHV	715411261338	Black/Chevron	15/16 In. (24 mm)	2' x 3'	Y	EA
414.1516x2x75CHV	715411261604	Black/Chevron	15/16 In. (24 mm)	2' x 75'	Y	RL
414.1516x3x10CHV	715411262151	Black/Chevron	15/16 In. (24 mm)	3' x 10'	N	EA
414.1516x3x20CHV	715411326150	Black/Chevron	15/16 In. (24 mm)	3' x 20'	N	EA
414.1516x3x5CHV	715411262144	Black/Chevron	15/16 In. (24 mm)	3' x 5'	Y	EA
414.1516x3x75CHV	715411262410	Black/Chevron	15/16 In. (24 mm)	3' x 75'	Y	RL
414.1516x4x75CHV	715411262953	Black/Chevron	15/16 In. (24 mm)	4' x 75'	Y	RL

