



<https://wearwell.com/>

UltraSoft Diamond-Plate SpongeCote - Gray

Group 414GY

Designed for comfort and optimized worker productivity, these mats are exceedingly popular among standing workers and have industrial strength for multiple shift operations. The double-thick Nitricell sponge base is a Nitrile composite for exceptional comfort, rebound and long life.

- NFSI Certified
- Nitricell sponge base
- 15/16" overall thickness
- Maximized standing area
- Also available in black, black w/ yellow borders and black w/ chevron borders
- **Need a different size?** 1' incremental lengths are available! [Simply give us a call, and we can help!](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material PVC Surface With Nitrile Infused Sponge

Recycled >50%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 - 6.2psi @ 25% =.24" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
414.1516x2x3GY	715411261390	Gray	15/16 In. (24 mm)	2' x 3'	Y	EA
414.1516x2x75GY	715411261666	Gray	15/16 In. (24 mm)	2' x 75'	Y	RL
414.1516x3x10GY	715411262212	Gray	15/16 In. (24 mm)	3' x 10'	N	EA
414.1516x3x5GY	715411262205	Gray	15/16 In. (24 mm)	3' x 5'	Y	EA
414.1516x3x75GY		Gray	15/16 In. (24 mm)	3' x 75'	Y	RL
414.1516x4x75GY		Gray	15/16 In. (24 mm)	4' x 75'	Y	RL