WWEARWELL



https://wearwell.com/

UltraSoft Diamond-Plate SpongeCote - Black with Yellow Borders

Group 414BYL

Designed for comfort and optimized worker productivity, these mats are exceedingly popular among standing workers and have industrial strength for multiple shift operations. The double-thick Nitricell sponge base is a Nitrile composite for exceptional comfort, rebound and long life.

- NFSI Certified
- Nitricell sponge base
- 15/16" overall thickness
- Maximized standing area
- Also available in gray, black and black w/ chevron borders
- **Need a different size?** 1' incremental lengths are available! <u>Simply give us a call, and we can help!</u>

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Nitrile Infused Sponge
Recycled	>50%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 - 6.2psi @ 25% =.24" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
414.1516x2x3BYL	715411261512	Black/Yellow	15/16 In. (24 mm)	2' x 3'	Υ	EA
414.1516x2x75BYL	715411261789	Black/Yellow	15/16 In. (24 mm)	2' x 75'	Υ	RL
414.1516x3x10BYL	715411262335	Black/Yellow	15/16 In. (24 mm)	3' x 10'	Υ	EA
414.1516x3x20BYL	715411765621	Black/Yellow	15/16 In. (24 mm)	3' x 20'	N	EA
414.1516x3x5BYL	715411262328	Black/Yellow	15/16 In. (24 mm)	3' x 5'	Υ	EA
414.1516x3x75BYL	715411262595	Black/Yellow	15/16 In. (24 mm)	3' x 75'	Υ	RL
414.1516x4x75BYL	715411263134	Black/Yellow	15/16 In. (24 mm)	4' x 75'	Υ	RL
414.1516x5x75BYL	715411621217	Black/Yellow	15/16 In. (24 mm)	5' x 75'	Υ	RL

6' x 75'

Υ

RL