



<https://wearwell.com/>

Diamond-Plate Nitricell SpongeCote with Stay-Put Finish Mat - Black

Group 815BK

Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. Stay-Put, a special finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. Stay-Put finally solves this decades old problem. Diamond-Plate Nitricell SpongeCote with Stay-Put Finish has taken our most premium UltraSoft products to the next level. This new "Gold Standard" has a tough diamond surface, extra-thick ergonomic build, and keeps mats safely in place.

- Stop sliding mats with Stay-Put Finish
- New 'Gold Standard' of matting
- Thick, premium ergonomics
- Unique polymer is permanently tacky and easy to remove
- Designed to prevent slips, trips, and falls
- Works right out of the box!
- Abrasion and chemical resistant surface
- Overall thickness 9/16" (14 mm)
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material PVC Surface With Nitrile Infused Sponge

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	7.1psi @ 25% = .15" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
815.916x2x3BK		Black	9/16 In. (14 mm)	2' x 3'	Y	EA
815.916x3x10BK		Black	9/16 In. (14 mm)	3' x 10'	N	EA

815.916x3x5BK		Black	9/16 In. (14 mm)	3' x 5'	Y		EA
815.916x3x75BK		Black	9/16 In. (14 mm)	3' x 75'	Y		Roll