



<https://wearwell.com/>

UltraSoft Diamond-Plate Nitricell SpongeCote with Stay-Put Finish Mat - Black

Group 814BK

Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. Stay-Put, a special non-slip finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. Stop sliding mats with Stay-Put Finish to finally solve this decades old problem. UltraSoft Diamond-Plate SpongeCote with Stay-Put Finish has taken our most premium UltraSoft products to the next level. This new "Gold Standard" has a tough diamond surface, extra-thick ergonomic build, and keeps mats safely in place.

- Stay-Put Finish stops mats from slipping and sliding
- New 'Gold Standard' of matting
- Thick, premium ergonomics
- Unique polymer is permanently tacky and easy to remove
- Designed to prevent slips, trips, and falls
- Works right out of the box!
- Abrasion and chemical resistant surface
- Overall thickness 15/16" (24 mm)
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Material PVC Surface With Nitrile Infused Sponge

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=13.20
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
814.1516x2x3BK		Black	15/16 In. (24 mm)	2' x 3'	Y	EA
814.1516x3x10BK		Black	15/16 In. (24 mm)	3' x 10'	N	EA

814.1516x3x5BK		Black	15/16 In. (24 mm)	3' x 5'	Y	EA
814.1516x3x75BK		Black	15/16 In. (24 mm)	3' x 75'	Y	Roll