
WWEARWELL



https://wearwell.com/

UltraSoft Tile-Top AM - Blue

Group 419BL

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and <u>chemical resistance</u> in dry areas.

- Lay-flat design Built-in trip prevention with beveled safety edges
- NFSI (National Floor Safety Institute) Certified
- Perfect mat for healthcare workstations and standing height desks
- Best Nitricell Sponge for extended performance of anti-fatigue mats
- 20% more standing area
- Available in multiple colors & sizes
- **Need a different size?** 1' incremental lengths are available! <u>Simply</u> give us a shout out!

Learn more about Tile-Top ergonomic matting here.

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result			
Flammability	MVSS 302 / 'A'; Rating			
Taber Abrasion	ASTM D 3884 / 1% loss			
Temperature Range	10 to 140 F			
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .17			
Compression Deflection	ASTM D575 - 5.2psi @ 25% =.22" distance compressed			
Tear Strength	Not Available			
ESD Rating	Not Available			
Dielectric Strength	Not Available			

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMBL	715411029709	Blue	7/8 In. (22 mm)	2' x 3'	Υ	EA
419.78x2X60AMBL	715411030668	Blue	7/8 In. (22 mm)	2' x 60'	Υ	RL
419.78x3X10AMBL	715411328109	Blue	7/8 In. (22 mm)	3' x 10'	N	EA
419.78x3X5AMBL	715411032600	Blue	7/8 In. (22 mm)	3' x 5'	Υ	EA
419.78x3X60AMBL	715411030064	Blue	7/8 In. (22 mm)	3' x 60'	Υ	RL
419.78x4X60AMBL		Blue	7/8 In. (22 mm)	4' x 60'	Υ	RL