



<https://wearwell.com/>

UltraSoft Tile-Top AM - Charcoal

Group 419CH

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and [chemical resistance](#) in dry areas.

- Features Best Nitricell Sponge for extended performance of anti-fatigue mats
- Wearwell brand Lay-flat design - Built-in trip prevention with beveled safety edges
- Works for workstations and standing height desks
- Available in multiple colors & sizes
- 20% more standing area
- NFSI Certified
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Tile-Top ergonomic matting [here](#).

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .17
Compression Deflection	ASTM D575 - 5.2psi @ 25% = .22" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMCH	715411033256	Charcoal	7/8 In. (22 mm)	2' x 3'	Y	EA
419.78x2X60AMCH	715411031689	Charcoal	7/8 In. (22 mm)	2' x 60'	Y	RL
419.78x3X10AMCH	715411106578	Charcoal	7/8 In. (22 mm)	3' x 10'	N	EA
419.78x3X5AMCH	715411032686	Charcoal	7/8 In. (22 mm)	3' x 5'	Y	EA
419.78x3X60AMCH	715411031757	Charcoal	7/8 In. (22 mm)	3' x 60'	Y	RL
419.78x4X60AMCH	715411029181	Charcoal	7/8 In. (22 mm)	4' x 60'	Y	RL

