



<https://wearwell.com/>

Tile-Top AM - Charcoal

Group 420CH

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and [chemical resistance](#) in dry areas.

- 2X the resilience and 3X more long lasting than off brand look-alikes
- Features tough and attractive abrasion and chemical resistant floor mat surface
- Floor mats are perfect for healthcare workstations and standing height desks
- Meets the ASTM G21 standard for anti-microbial properties
- NFSI (National Floor Safety Institute) Certified
- Available in multiple marble top colors

Learn more about Tile-Top ergonomic matting [here](#).

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .17
Compression Deflection	ASTM D575 - 7.5psi @ 25% = .22" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
420.12x2x3AMCH	715411168668	Charcoal	1/2 In. (13 mm)	2' x 3'	Y	EA
420.12x2x60AMCH	715411168439	Charcoal	1/2 In. (13 mm)	2' x 60'	Y	RL
420.12x3x10AMCH	715411106561	Charcoal	1/2 In. (13 mm)	3' x 10'	N	EA
420.12x3x5AMCH	715411168347	Charcoal	1/2 In. (13 mm)	3' x 5'	Y	EA
420.12x3x60AMCH	715411168576	Charcoal	1/2 In. (13 mm)	3' x 60'	Y	RL