## **WWEARWELL**



https://wearwell.com/

## Tile-Top AM - Gray

**Group 420GY** 

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and <u>chemical resistance</u> in dry areas.

- Features tough and attractive abrasion and chemical resistant floor mat surface
  - 2X the resilience and 3X more long lasting than off brand look-alikes
  - Perfect for healthcare workstations and standing height desks
  - Meets the ASTM G21 standard for anti-microbial properties
  - NFSI (National Floor Safety Institute) Certified
  - Available in multiple marble top colors & sizes

Learn more about Tile-Top ergonomic matting <a href="here">here</a>.

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
<b>Customization Options</b>	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .17
Compression Deflection	ASTM D575 - 7.5psi @ 25% = .22" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
420.12x2x3AMGY	715411333622	Gray	1/2 In. (13 mm)	2' x 3'	Υ	EA
420.12x2x60AMGY	715411549146	Gray	1/2 In. (13 mm)	2' x 60'	Υ	RL
420.12x3x10AMGY	715411328802	Gray	1/2 In. (13 mm)	3' x 10'	N	EA
420.12x3x5AMGY	715411334759	Gray	1/2 In. (13 mm)	3' x 5'	Υ	EA
420.12x3x60AMGY	715411547180	Gray	1/2 In. (13 mm)	3' x 60'	Υ	RL