WWEARWELL



https://wearwell.com/

UltraSoft Tile-Top Nitricell AM SpongeCote with Stay-Put Finish Mat - Gray

Group 819GY

Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. <u>Stay-Put</u>, a special finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. Stay-Put finish finally solves this decades old problem. Tile-Top AM with Stay-Put Finish has a tough surface and thick ergonomic build. With Anti-Microbial properties through and through, Tile-Top AM takes your protection to the next level, <u>preventing slips</u>, trips, falls- and contamination.

- Stay-Put finish prevents mats from sliding on any floor
- Premium extra thick Anti-Microbial sponge
- Anti-Microbial through and through
- Designed to prevent slips, trips & falls
- Maximized standing area
- Overall thickness 7/8" (22.2mm)
- **Need a different size?** 1' incremental lengths are available! <u>Simply give us a shout out!</u>

Learn more about the ergonomics and benefits of Stay-Put Finish in our blog - #STOPSLIDINGMATS.

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry Floors
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .17
Compression Deflection	6.3psi @ 25% =.22" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
819.78x2x3AMGY		Gray	7/8 In. (22 mm)	2' x 3'	Υ	EA
819.78x2X60AMGY		Gray	7/8 In. (22 mm)	2' x 60'	N	Roll

819.78x3X5AMGY	Gray	7/8 In. (22 mm)	3' x 5'	Υ	EA	
819.78x3X60AMGY	Gray	7/8 In. (22 mm)	3' x 60'	Υ	Roll	