



<https://wearwell.com/>

Tuf Sponge - Black with Yellow Borders

Group 451BYL

Wearwell's Tuf Sponge is for use in all dry work areas, an excellent choice for practical and economical comfort. Made from blown PVC sponge, Tuf Sponge reduces floor hardness up to 50% and can easily be custom cut to fit your work areas. 3/8" overall thickness with safety rounded edges.

- Economic comfort for light industrial applications
- Safety rounded edges
- Can easily be cut to size on-site
- Overall thickness 3/8"
- [Contact us for pricing](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C1 - Custom Length

Solid or Drainage Solid

Material PVC Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	DOC FF1-70 / Flame Retardant Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .94 / Wet: COF = .72
Compression Deflection	ASTM D575 / .205 @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
451.38x2x3BYL	715411244034	Black/Yellow	3/8 In. (10 mm)	2' x 3'	Y	EA
451.38x2x60BYL	715411243945	Black/Yellow	3/8 In. (10 mm)	2' x 60'	Y	RL
451.38x3x12BYL	715411244348	Black/Yellow	3/8 In. (10 mm)	3' x 12'	Y	EA
451.38x3x5BYL	715411244317	Black/Yellow	3/8 In. (10 mm)	3' x 5'	Y	EA
451.38x3x60BYL	715411244218	Black/Yellow	3/8 In. (10 mm)	3' x 60'	Y	RL
451.38x4x60BYL	715411244485	Black/Yellow	3/8 In. (10 mm)	4' x 60'	Y	RL