



<https://wearwell.com/>

Tuf Sponge - Gray

Group 451GY

Wearwell's Tuf Sponge is for use in all dry work areas, an excellent choice for practical and economical comfort. Made from blown PVC sponge, Tuf Sponge reduces floor hardness up to 50% and can easily be custom cut to fit your work areas. 3/8" overall thickness with safety rounded edges.

- Economic comfort for light industrial applications
- Safety rounded edges
- Can easily be cut to size on-site
- Overall thickness 3/8"
- [Contact us for pricing](#)

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry Floors

Customization Options C1 - Custom Length

Solid or Drainage Solid

Material PVC Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	DOC FF1-70 / Flame Retardant Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .94 / Wet: COF = .72
Compression Deflection	ASTM D575 / .205 @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
451.38x2x3GY	715411244089	Gray	3/8 In. (10 mm)	2' x 3'	Y	EA
451.38x2x60GY	715411243990	Gray	3/8 In. (10 mm)	2' x 60'	Y	RL
451.38x3x12GY	715411244362	Gray	3/8 In. (10 mm)	3' x 12'	Y	EA
451.38x3x5GY	715411244355	Gray	3/8 In. (10 mm)	3' x 5'	Y	EA
451.38x3x60GY	715411244263	Gray	3/8 In. (10 mm)	3' x 60'	Y	RL
451.38x4x60GY	715411244539	Gray	3/8 In. (10 mm)	4' x 60'	Y	RL