



<https://wearwell.com/>

Smooth Military Switchboard Matting Type I - Blue

Group ML710-MATBL

Specially treated for flooring applications, this non-conductive matting meets Mil. Spec. 15562-G, Type I. When installing several widths of matting side-by-side, it is important to seal the seams to ensure reliable and consistent insulative properties. For best results, use professional floor installers. They have experience and machinery designed to bond this material.

- Designed for permanent installation using any vinyl-compatible mastic adhesive
- Non-conductive

Wearwell Categories Non-Conductive Accessory

Suitable Environment Dry Floors

Customization Options C1 - Custom Length

Solid or Drainage Solid

Material PVC

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	Passes Mil, 15562-G and FMVSS 302
Taber Abrasion	Not Available
Temperature Range	ASTM D1056 -20 to 160 degrees F
Coefficient of Friction	ASTM F1677 / Dry: COF = .79
Compression Deflection	Not Available
Tear Strength	ASTM D412 Die C results: 1212 psi
ESD Rating	Not Applicable
Dielectric Strength	Surface conforms to MIL-DTL-15562G, Type II, 30,000 volts. (Recommended Max Usage up to 3000 volts)

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
710.18x3x75MBL	715411012077	Blue	1/8 In. (3 mm)	3' x 75'	Y	RL