



<https://wearwell.com/>

Electrically Conductive, Diamond-Plate

Group 785-DP

Electrically Conductive Runner is the ideal floor runner for areas where static prevention is a priority. Can be rolled out for long aisle ways or cut to size for specific workstations. Use Electrically Conductive Runner to protect sensitive equipment or eliminate static annoyance. A grounding snap is included on each mat, and grounding is highly recommended for optimum mat performance.

NOTE: Must be grounded with a ground cord (793-Cord) and users must wear a heel grounder (793-Heel)

- Treated surface drains static electricity from personnel
- Available in Smooth or Diamond-Plate surface pattern
- Overall thickness, Smooth 3/32" or Diamond-Plate 5/32"
- Grounding snap is attached to the corner of each mat (NOTE: Mat must be grounded with a ground cord; workers must wear Heel Grounder or shoes with conductive soles)

◦ **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about ESD flooring and matting in our blog - [ESD 101: Everything You Need to Know About ESD Mats, Flooring, and Work Surfaces.](#)

Wearwell Categories	Runner
Suitable Environment	Dry Floors
Customization Options	C1 - Custom Length
Solid or Drainage	Solid
Material	PVC
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: 1×10^3 - 1×10^6 (meets ANSI/ESD 20.20 requirements)
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
785.532x3x10DPBK		Black	5/16 In. (4 mm)		Y	EA
785.532x3x5DPBK		Black	5/16 In. (4 mm)		Y	EA
785.532x3x75DPBK	715411603527	Black	5/16 In. (4 mm)	3' x 75'	Y	RL

785.532X4X75DPBK		Black	5/16 In. (4 mm)		N		EA
------------------	--	-------	-----------------	--	---	--	----