

24/Seven® LockSafe® MAX Male Edging - Yellow

Group 581.MGRYL



<https://wearwell.com/>

[24/SEVEN® LockSafe® MAX](#) male edging is Grease Resistant and securely interlocks with 24/SEVEN® LockSafe® MAX modular tiles. Yellow edging acts as a visual cue and smooth transition for foot traffic. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or wet areas where the primary liquid is water.

For use with 24/Seven Locksafe MAX series products only.

- For dry areas or areas with water
- Grease-resistant (Natural Rubber)
- 4 in. x 36 in. (8 cm x 91 cm)
- Overall thickness 1 in (25 mm)
- [Corners](#) and [female](#) edging available
- U.S. PATENT No. D882,293 S

Wearwell Categories	Anti-Fatigue Flooring
Suitable Environment	Dry Floors
Customization Options	C3
Solid or Drainage	Solid
Material	GR/Natural Rubber
Recycled	25%
Warranty	1 Year

Property	Test / Result
Flammability	testvaluebecauseofsemicolon
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: .90 / Wet .020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available