



<https://wearwell.com/>

## 24/Seven® LockSafe® MAX Corner - Yellow

Group 581.GRYL-CS4

**For use with 24/SEVEN® LockSafe® MAX tiles and edging,** these corners connect without cutting or hassle! Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or wet areas where the primary liquid is water.

- For dry areas or areas with water
- Grease Resistant (Natural Rubber)
- 4 in. x 4 in. (8 cm x 9 cm)
- Overall thickness 1 in (25 mm)
- Also available in black
- Male and female edging available
- U.S. PATENT No. D882

|                              |                       |
|------------------------------|-----------------------|
| <b>Wearwell Categories</b>   | Anti-Fatigue Flooring |
| <b>Suitable Environment</b>  | Dry Floors            |
| <b>Customization Options</b> | C3                    |
| <b>Solid or Drainage</b>     | Solid                 |
| <b>Material</b>              | GR/Natural Rubber     |
| <b>Recycled</b>              | 25%                   |
| <b>Warranty</b>              | 1 year                |

| Property                | Test / Result                           |
|-------------------------|---|
| Flammability            | MVSS 302 / 'A'; Rating                  |
| Taber Abrasion          | Federal Standard 191 Modified / 1% loss |
| Temperature Range       | 10 to 140 F                             |
| Coefficient of Friction | ASTM F1677 / Dry: .90 / Wet .020        |
| Compression Deflection  | Not Applicable                          |
| Tear Strength           | Not Applicable                          |
| ESD Rating              | Not Applicable                          |
| Dielectric Strength     | Not Applicable                          |