## **WEARWELL**



## Blue ErgoDeck® General Purpose Solid

Group 566-BL

A comfortable, ergonomic floor that will withstand heavy use. The patented LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose addresses worker health and comfort in areas with primarily foot traffic and light cart traffic.

• U.S. PATENT NO. D502

Anti-Fatigue Flooring
Dry Floors, Wet Area, Oily
C3 - Full Custom (Length
Solid
PVC
>80%
Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42
Compression Deflection	ASTM D575-91 /14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
566.78x18x18BL-CS10	715411787210	Blue	7/8 In. (22 mm)	18" x 18"	Y	CS-10