



<https://wearwell.com/>

## 24/Seven GR (Grease Resistant) Female Edging - Black

### Group 572-FGRBK

24/Seven GR (Grease Resistant) female edging securely interlocks with 24/Seven GR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry Floors, Wet Area, Slippery

**Customization Options** C3 - Full Custom (Length

**Solid or Drainage** Solid

**Material** Grease Resistant Natural Rubber (GR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = 020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available