



<https://wearwell.com/>

## 24/Seven CFR Female Edging - Yellow

### Group 572-FCFRYL

24/Seven CFR (Cutting Fluid Resistant) female edging securely interlocks with 24/Seven CFR rubber floor tiles. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry Floors, Wet Area, Oily, Slippery

**Customization Options** C3 - Full Custom (Length

**Solid or Drainage** Solid

**Material** Cutting Fluid Resistant Rubber (CFR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = 020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available