



ErgoDeck® Illuminate System

Group 566-ILL

ErgoDeck® Illuminate tiles offer a convenient way to lighten up poorly lit work areas from the floor up. Each tile can accommodate up to five Illuminate channels that can house most LED lighting systems available in the marketplace.

- U.S. PATENT NO. D502

<https://wearwell.com/>

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry Floors

Customization Options C3 - Full Custom (Length

Solid or Drainage Solid

Material Aluminum/Polycarbonate compound and PVC

Recycled >80%

Warranty 1 year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42
Compression Deflection	ASTM D575-91 /14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
566.CH.Chan1-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN10-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.Chan2-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.Chan3-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.Chan4-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN5-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN6-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN7-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN8-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.CH.CHAN9-CS10	715411698387		7/8 In. (22 mm)	18" x 18"	Y	CS-10