



<https://wearwell.com/>

24/Seven® LockSafe® Interlocking Rubber Floor Tiles - Drainage GR w/ Gritshield®

Group 586-GR

24/SEVEN® LockSafe® GR with GRITSHIELD® is the perfect anti-fatigue solution for the slickest areas. The drainage design is ideal for dealing with liquids and overspray. These large 3'x3' rubber tiles interlock interlock with no tools required, making installation quick and easy. Use optional edging and corners where you need them. The patented Positive Interlock System provides a secure connection in all directions, so you don't have to worry about tiles coming apart, even with heavy traffic. Sections can be easily rolled up and moved for maintenance. Tiles hold together and only come apart when you want them to.

- Grit provides extra traction for grease, water, and dusty areas
- Positive interlock system keeps tiles together in use
- NBR version available for petroleum based fluids
- Easy to maintain, simply roll up and move
- Overall thickness 5/8" (16 mm) provides fantastic support

Wearwell Categories

Suitable Environment	Dry Floors, Wet Area, Oily
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	GR/Natural Rubber
Recycled	20%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.1 / Wet COF = .96
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
586.58x3x3GRBK	715411024025	Black	5/8 In. (16 mm)	3' x 3'	Y	EA