



<https://wearwell.com/>

24/Seven® Solid - Interlocking Rubber Floor Tiles

Group 570

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges.

Available in 3 different rubber compounds based on environmental exposures:

- GR - for water or dry debris
- CFR - for mineral oil-based fluids
- NBR - for petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Wearwell Categories

Suitable Environment	Dry Floors, Wet Area
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	Natural Rubber (GR), Cutting Fluid Resistant Rubber (CFR), or Nitrile Rubber (NBR)
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .68
Compression Deflection	ASTM D575 - 25.3 psi @ 15% = .1" distance compressed
Tear Strength	Not Rated
ESD Rating	Not Rated
Dielectric Strength	Not Rated